arXiv:1403.7933v1 [math.CO] 31 Mar 2014

Additive codes over $GF(4)$ from circulant graphs*

Xueliang Li, Yaping Mao, Meiqin Wei
Nankai University, Tianjin 300071, China
Center for Combinatorics and LPMC-TJKLC
E-mails: lxl@nankai.edu.cn; maoyaping@ymail.com; weimeiqin@mail.nankai.edu.cn
and
Ruihu Li
The air force engineering University
Institute of science, Xi'an 710051, China
E-mail: liruihu@aliyun.com

Abstract

In 2006, Danielsen and Parker [8] proved that every self-dual additive code over $GF(4)$ is equivalent to a graph code. So, graph is an important tool for searching (proposed) optimum codes. In this paper, we introduce a new method of searching (proposed) optimum additive codes from circulant graphs.

AMS Subject Classification 2010: 94B05, 05C50, 05C25.

1 Introduction

We define $GF(4) = \{0, 1, \omega, \omega^2\}$, where $\omega^2 = 1 + \omega$. An additive code C over $GF(4)$ of length n is an additive subgroup of $GF(4)$. Clearly, $\mathcal{C}$ contains codewords for some $0 \leq k \leq 2n$, and can be defined by a $k \times n$ generator matrix, with entries from $GF(4)$, whose rows span $\mathcal{C}$ additively. We call $\mathcal{C}$ an $(n, 2^k)$ code. The *Hamming weight* of $u \in GF(4)$, denoted by $wt(u)$, is the number of non zero components of u. The *Hamming distance* between two vectors $u = (u_1, \cdots, u_n)$, $v = (v_1, \cdots, v_n)$ is $wt(u - v)$. The *minimum distance* d of a code is defined as the smallest possible distance between pairs of distinct codewords. The *conjugation* of $x \in GF(4)$ is defined by $\bar{x} = x^2$, and the *trace map* is defined by $Tr(x) = x + \bar{x}$. The *Hermitian trace inner product* of $u = (u_1, \cdots, u_n)$ and $v = (v_1, \cdots, v_n)$, with $u_i, v_j \in GF(4)$, is given by $u * v = Tr(u \cdot \bar{v}) = \sum_{i=1}^{n} Tr(u_i \bar{v_i}) = \sum_{i=1}^{n} (u_i v_i^2 + u_i^2 v_i)$. We define *the dual of the code* $\mathcal{C}$ with respect to the Hermitian trace inner product, $\mathcal{C}^{\perp} = \{u \in GF(4) \mid u * c = 0 \ for \ all \ c \in \mathcal{C}\}$. Then $\mathcal{C}$ is *self-orthogonal* if $\mathcal{C} \subseteq \mathcal{C}^{\perp}$, and $\mathcal{C}$ is *self-dual* if $\mathcal{C} = \mathcal{C}^{\perp}$. A graph code is an additive code over

*Supported by "973" program No.2013CB834204.

$GF(4)$ that has a generator matrix of the form $\mathcal{C} = \Gamma + \omega I$, where I is the identity matrix and Γ is the adjacency matrix of a simple undirected graph.

A code is called *optimum* if it meets both lower and upper bounds in the Code Tables, and a *proposed optimum* code if it only meets the lower bound in the Code Tables. The distribution of a code is the sequence $(A_0, A_1, \cdots, A_n)$, where A_i is the number of codewords of weight i. The *weight enumerator* of the code is the polynomial

$$W(z) = \sum_{i=0}^{n} A_i z^i.$$

Let us now introduce some concepts and notions from Graph Theory. An *undirected graph* $\Gamma = (V, E)$ is a set $V(\Gamma) = \{v_1, v_2, \cdots, v_n\}$ of vertices together with a collection $E(\Gamma)$ of edges, where each edge is an unordered pair of vertices. The vertices v_i and v_j are *adjacent* if $\{v_i, v_j\}$ is an edge. Then v_j is a *neighbour* of v_i. All the neighbours of vertex v_i in graph Γ form the *neighbourhood* of v_i, and it is denoted by $N_\Gamma(v_i)$. The *degree of a vertex* v is the number of vertices adjacent to v. A graph is *k-regular* if all vertices have the same degree k. The *adjacency matrix* $A = (a_{ij})$ of a graph $\Gamma = (V, E)$ is a symmetric $(0, 1)$-matrix defined as follows: $a_{i,j} = 1$ if the i-th and j-th vertices are adjacent, and $a_{i,j} = 0$ otherwise.

Circulant graphs and their various applications are the objects of intensive study in computer science and discrete mathematics, see [1, 2, 11, 14]. Recently, Monakhova published a survey paper on this subject, see [13]. Let $S = \{a_1, a_2, \cdots, a_k\}$ be a set of integers such that $0 < a_1 < \cdots < a_k < \frac{n+1}{2}$ and let the vertices of an n-vertex graph be labelled $0, 1, 2, \cdots, n-1$. Then the *ciculant graph* $C(n, S)$ has $i \pm a_1, i \pm a_2, \cdots, i \pm a_k \ (mod\ n)$ adjacent to each vertex i. A *circulant matrix* is obtained by taking an arbitrary first row, and shifting it cyclically one position to the right in order to obtain successive rows. We say that a circulant matrix is generated by its first row. Formally, if the first row of an n-by-n circualant matrix is $a_0, a_1, \cdots, a_{n-1}$, then the $(i, j)^{th}$ element is a_{j-i}, where subscripts are taken modulo n. The term circulant graph arises from the fact that the adjacency matrix for such a graph is a circulant matrix. For example, Figure 1 shows the circulant graph $C(9, \{1, 2, 3\})$.



Figure 1: The circulant graph $C(9, \{1, 2, 3\})$

In 2002, Tonchev [16] first set up a relationship between a linear binary code and the adjacency matrix of an undirected graph. In 2006, Danielsen and Parker [8] proved that every self-

dual additive code over $GF(4)$ is equivalent to a graph code. Recently, finding optimum codes from graphs has received a wide attention of many researchers, see [4, 5, 6, 7, 8, 9, 10, 16, 17]. In [8], Danielsen and Parker showed that two codes are equivalent if and only if the corresponding graphs are equivalent with respect to local complementation and graph isomorphism. They used these facts to classify all codes of length up to 12. In 2012, Danielsen [4] focused his attention on additive codes over $GF(9)$ and transformed the problem of code equivalence into a problem of graph isomorphism. By an extension technique, they classified all optimal codes of lengths 11 and 12. In fact, a computer search reveals that circulant graph codes usually contain many strong codes, and some of these codes have highly regular graph representations, see [17]. In [4], Danielsen obtained some optimum additive codes from circulant graphs in 2005. Later, Varbanov investigated additive circulant graph codes over $GF(4)$, see [17].

In this paper, we find out some optimum additive codes from some special circulant graphs. This paper is organized as follows. In Section 2, we propose a new method to find additive optimum codes from circulant graphs. Inspired by the optimum additive codes obtained by Danielsen [4], we focus on the dense circulant graphs and get some optimum additive codes in Section 3.

2 New codes from sparse circulant graphs

In fact, Glynn et al. [9] obtained an optimum code from a circulant graph, called 5-valent graph. Recall that Γ_{12} is a circulant graph of order 12; see Figure 1 (a).



Figure 1: (a) a 5-valent graph Γ_{12}; (b) the circulant graph Γ_{24}.

Let $V(\Gamma_{12}) = \{u_1, u_2, \cdots, u_{12}\}$. For the vertex u_1, we let $E_1 = \{v_1v_2, v_1v_4, v_1v_7, v_1v_{10}, v_1v_{12}\} \subseteq E(\Gamma_{12})$. For the vertex u_2, we just rotate the above vertices and edges, that is, we only permit the existence of the set $E_2 = \{v_2v_3, v_2v_4, v_2v_6, v_2v_{10}, v_2u_{12}\} \subseteq E(G)$ of edges. For each vertex $u_i \in V(\Gamma) \setminus \{u_1, u_2\} = \{u_3, u_4, \cdots, u_{12}\}$, we can also obtained the sets E_i $(3 \leq i \leq 17)$ of edges. Observe that $E(\Gamma_{12}) = \bigcup_{i=1}^{12} E_i$.

The adjacency matrix of the graph Γ_{12} is the following circulant matrix.

$$A_{12} = \begin{pmatrix} 0 & 1 & 0 & 1 & 0 & 0 & 1 & 0 & 0 & 1 & 0 & 1 \\ 1 & 0 & 1 & 0 & 1 & 0 & 0 & 1 & 0 & 0 & 1 & 0 \\ 0 & 1 & 0 & 1 & 0 & 1 & 0 & 0 & 1 & 0 & 0 & 1 \\ 1 & 0 & 1 & 0 & 1 & 0 & 1 & 0 & 0 & 1 & 0 & 0 \\ 0 & 1 & 0 & 1 & 0 & 1 & 0 & 1 & 0 & 0 & 1 & 0 \\ 0 & 0 & 1 & 0 & 1 & 0 & 1 & 0 & 1 & 0 & 0 & 1 \\ 1 & 0 & 0 & 1 & 0 & 1 & 0 & 1 & 0 & 1 & 0 & 0 \\ 0 & 1 & 0 & 0 & 1 & 0 & 1 & 0 & 1 & 0 & 1 & 0 \\ 0 & 0 & 1 & 0 & 0 & 1 & 0 & 1 & 0 & 1 & 0 & 1 \\ 1 & 0 & 0 & 1 & 0 & 0 & 1 & 0 & 1 & 0 & 1 & 0 \\ 0 & 1 & 0 & 0 & 1 & 0 & 0 & 1 & 0 & 1 & 0 & 1 \\ 1 & 0 & 1 & 0 & 0 & 1 & 0 & 0 & 1 & 0 & 1 & 0 \end{pmatrix}$$

The above matrix can also be obtained by the following vector

$$\alpha_{12} = (0, 1, 0, 1, 0, 0, 1, 0, 0, 1, 0, 1).$$

Observe that this vector just corresponds to the set E_1 of edges, which is an expression of the adjacent relation about the vertex u_1. We conclude that a 5-valent graph can be determined by the edge set E_1, and the adjacency matrix of this graph is determined by the above vector α_{12}.

Furthermore, the matrix $A_{12} + \omega I$ is

$$A'_{12} = A_{12} + \omega I = \begin{pmatrix} \omega & 1 & 0 & 1 & 0 & 0 & 1 & 0 & 0 & 1 & 0 & 1 \\ 1 & \omega & 1 & 0 & 1 & 0 & 0 & 1 & 0 & 0 & 1 & 0 \\ 0 & 1 & \omega & 1 & 0 & 1 & 0 & 0 & 1 & 0 & 0 & 1 \\ 1 & 0 & 1 & \omega & 1 & 0 & 1 & 0 & 0 & 1 & 0 & 0 \\ 0 & 1 & 0 & 1 & \omega & 1 & 0 & 1 & 0 & 0 & 1 & 0 \\ 0 & 0 & 1 & 0 & 1 & \omega & 1 & 0 & 1 & 0 & 0 & 1 \\ 1 & 0 & 0 & 1 & 0 & 1 & \omega & 1 & 0 & 1 & 0 & 0 \\ 0 & 1 & 0 & 0 & 1 & 0 & 1 & \omega & 1 & 0 & 1 & 0 \\ 0 & 0 & 1 & 0 & 0 & 1 & 0 & 1 & \omega & 1 & 0 & 1 \\ 1 & 0 & 0 & 1 & 0 & 0 & 1 & 0 & 1 & \omega & 1 & 0 \\ 0 & 1 & 0 & 0 & 1 & 0 & 0 & 1 & 0 & 1 & \omega & 1 \\ 1 & 0 & 1 & 0 & 0 & 1 & 0 & 0 & 1 & 0 & 1 & \omega \end{pmatrix}$$

This matrix is also a circulant matrix, which can be obtained by the following vector

$$\alpha'_{12} = (\omega, 1, 0, 1, 0, 0, 1, 0, 0, 1, 0, 1).$$

From the matrix $A_{12} + \omega I$, we can get a graph code $\mathcal{C}_{12}$. From the Code Tables, we know that $(12, 2^{12}, 6)$ is an optimum additive code over $GF(4)$. Then $n = 12$ and $d_{12} = 6$, where d_{12} is the minimum distance of the code $\mathcal{C}_{12}$.

The above statement suggests the following method for finding optimum codes.

Step 1. Given an even integer n. Denote by L_n the lower bound of the additive code $(n,2^n)$ over $GF(4)$. From Code Tables, we find the exact value of L_n for the given n. We now construct a circulant graph Γ_n by a set E_1 of edges as follows.

Step 1.1. Arrange the vertices from $V(\Gamma_n) = \{u_1, u_2, \cdots, u_n\}$ in a circular order.

Step 1.2. Determine the set E_1 of edges satisfying $|E_1| = L_n - 1$ or $|E_1| = L_n + 1$, where $E_1 = N_{\Gamma_n}(u_1)$. If $|E_1| = L_n + 1$, then

$$\begin{aligned} E_1 &= \{u_1u_2, u_1u_3\} \cup \{u_1u_{3+2\cdot 1}, u_1u_{3+2\cdot 2}, \cdots, u_1u_{3+2\cdot\frac{L_n-4}{2}}, \} \cup \{u_1u_{\frac{n}{2}+1}\} \\ &\quad \cup \{u_1u_{n-1-2\cdot\frac{L_n-4}{2}}, \cdots, u_1u_{n-1-2\cdot 2}, u_1u_{n-1-2\cdot 1}\} \cup \{u_1u_n, u_1u_{n-1}\} \\ &= \{u_1u_2, u_1u_3\} \cup \{u_1u_5, u_1u_7, \cdots, u_1u_{L_n-1}\} \cup \{u_1u_{\frac{n}{2}+1}\} \\ &\quad \cup \{u_1u_{n-L_n+3}, \cdots, u_1u_{n-5}, u_1u_{n-3}\} \cup \{u_1u_n, u_1u_{n-1}\} \end{aligned}$$

If $|E_1| = L_n - 1$, then

$$\begin{aligned} E_1 &= \{u_1u_2, u_1u_3\} \cup \{u_1u_{3+2\cdot 1}, u_1u_{3+2\cdot 2}, \cdots, u_1u_{3+2\cdot\frac{L_n-6}{2}}, \} \cup \{u_1u_{\frac{n}{2}+1}\} \\ &\quad \cup \{u_1u_{n-1-2\cdot\frac{L_n-6}{2}}, \cdots, u_1u_{n-1-2\cdot 2}, u_1u_{n-1-2\cdot 1}\} \cup \{u_1u_n, u_1u_{n-1}\} \\ &= \{u_1u_2, u_1u_3\} \cup \{u_1u_5, u_1u_7, \cdots, u_1u_{L_n-3}\} \cup \{u_1u_{\frac{n}{2}+1}\} \\ &\quad \cup \{u_1u_{n-L_n+5}, \cdots, u_1u_{n-5}, u_1u_{n-3}\} \cup \{u_1u_n, u_1u_{n-1}\} \end{aligned}$$

Step 2. By the edge set E_1, we write the vector α_n corresponding to E_1. If $|E_1| = L_n + 1$, then

$$\begin{array}{rc} & \begin{array}{cccccccccccccccccccccc} u_2 & u_3 & & u_5 & & & u_{L_n-1} & & & & & u_{\frac{n}{2}+1} & & & & & u_{n-L_n+3} & & & & u_{n-3} & u_{n-1} & u_n \end{array} \\ \alpha_n = & \Big(\begin{array}{cccccccccccccccccccccc} 0 & 1 & 1 & 0 & 1 & \cdots & 0 & 1 & 0 & 0 & \cdots & 0 & 1 & 0 & 0 & \cdots & 0 & 1 & 0 & \cdots & 1 & 0 & 1 & 1 \end{array} \Big) \end{array}$$

If $|E_1| = L_n - 1$, then

$$\begin{array}{rc} & \begin{array}{cccccccccccccccccccccc} u_2 & u_3 & & u_5 & & & u_{L_n-3} & & & & & u_{\frac{n}{2}+1} & & & & & u_{n-L_n+5} & & & & u_{n-3} & u_{n-1} & u_n \end{array} \\ \alpha_n = & \Big(\begin{array}{cccccccccccccccccccccc} 0 & 1 & 1 & 0 & 1 & \cdots & 0 & 1 & 0 & 0 & \cdots & 0 & 1 & 0 & 0 & \cdots & 0 & 1 & 0 & \cdots & 1 & 0 & 1 & 1 \end{array} \Big) \end{array}$$

Step 3. Change the first component of the vector α_n to ω. Denote by α'_n the new vector. We generate a circulant matrix A'_n from α'_n.

$$\alpha'_n = (\omega, 1, 1, 0, 1, 0, 1, \cdots, 0, 1, 0, 0, \cdots, 0, 1, 0, 0, \cdots, 0, 1, 0, 1, 0, \cdots, 1, 0, 1, 1)$$

Step 4. By Algorithm 1, we obtain the minimum distance d_n of the code $\mathcal{C}_n$ and determine whether $d_n = L_n$. If so, the code $\mathcal{C}_n$ is a proposed optimum code.

Below is an algorithm (running in SAGE). For more details, we refer to [15].

Algorithm 1: Minimum distance of a circulant graph code

Input: the value of n, the generator vector α_n of a circulant graph code $\mathcal{C}_n$
Objective: the minimum distance of the circulant graph code $\mathcal{C}_n$
1. input the value of n, the generator vector $\alpha_n = (b_1, b_2, \cdots, b_n)$;
2. obtain the generator matrix G of the circulant graph code $\mathcal{C}_n$;
3. get the minimum distance of the circulant graph code $\mathcal{C}_n$.

Take an example, let $n = 24$ and $\alpha_n = (\omega, 1, 1, 0, 1, 0, 0, 0, 0, 0, 0, 0, 1, 0, 0, 0, 0, 0, 0, 0, 1, 0, 1, 1)$. The algorithm details are stated as follows:

Program:

$F. < x >= GF(4,' x')$
$n = 24$;
$a = [x, 1, 1, 0, 1, 0, 0, 0, 0, 0, 0, 0, 1, 0, 0, 0, 0, 0, 0, 0, 1, 0, 1, 1]$
$m = matrix(F, n, n, [[a[(i-k)\%n] \text{ for } i \text{ in } [0..(n-1)]] \text{ for } k \text{ in } [0..n-1]])$;
$f = lambda\ s : sum(map(lambda\ x : m[x], s))$;
$s = [\ ]$;
for k in [1..8]:
    $t = min([n - list(i).count(0) \text{ for } i \text{ in Subsets } (range(n), k).map(f)])$;
    $s+ = [t]$;
    print s;

Output: [8]
[8, 8]
[8, 8, 10]
[8, 8, 10, 8]
[8, 8, 10, 8, 8]
[8, 8, 10, 8, 8, 8]
[8, 8, 10, 8, 8, 8, 8]
[8, 8, 10, 8, 8, 8, 8, 10]

Result: The minimum element of the last array is the minimum distance d_{24} of the code $\mathcal{C}_{24}$, that is, $d_{24} = 8$.

Inspired by the graph code $\mathcal{C}_1$ which corresponds to the 5-valent graph, we hope to find out some other optimum additive codes for $n = 24$.

Step 1. Recall L_{24} is the lower bound of the additive code $(24, 2^{24})$ over $GF(4)$. From Code Tables, we find the exact value of L_{24}, $L_{24} = 8$. We now construct a circulant graph Γ_{24} by a set E_1 of edges as follows.

Step 1.1. Arrange the vertices from $V(\Gamma_n) = \{u_1, u_2, \cdots, u_{24}\}$ in a circular order.

Step 1.2. Determine the set E_1 of edges satisfying $|E_1| = L_{24} - 1 = 7$ or $|E_1| = L_{24} + 1 = 9$,

where $E_1 = N_{\Gamma_n}(u_1)$. If $|E_1| = 9$, then

$$E_1 = \{u_1u_2, u_1u_3, u_1u_5, u_1u_7, u_1u_{13}, u_1u_{19}, u_1u_{21}, u_1u_{23}, u_1u_{24}\}$$

If $|E_1| = 7$, then

$$E_1 = \{u_1u_2, u_1u_3, u_1u_5, u_1u_{13}, u_1u_{21}, u_1u_{23}, u_1u_{24}\}.$$

In this case, the circulant graph Γ_{24} can be found out; see Figure 1 (b).

Step 2. By the edge set E_1, we write the vector α_{24} corresponding to E_1. If $|E_1| = 9$, then

$$\alpha_{24} = (0,1,1,0,1,0,1,0,0,0,0,0,1,0,0,0,0,0,1,0,1,0,1,1).$$

If $|E_1| = 7$, then

$$\alpha_{24} = (0,1,1,0,1,0,0,0,0,0,0,0,1,0,0,0,0,0,0,0,1,0,1,1).$$

Step 3. Change the first component of the vector α_{24} to ω. Denote by α'_{24} the new vector. We generate a circulant matrix $A'_{24}(A''_{24})$ from $\alpha'_{24}(\alpha''_{24})$.

$$\alpha'_{24} = (\omega,1,1,0,1,0,1,0,0,0,0,0,1,0,0,0,0,0,1,0,1,0,1,1)$$
$$\alpha''_{24} = (\omega,1,1,0,1,0,0,0,0,0,0,0,1,0,0,0,0,0,0,0,1,0,1,1).$$

Step 4. By Algorithm 1, we obtain the minimum distance $d'_{24} = d''_{24} = 8$. Therefore, both $\mathcal{C}'_{24}$ and $\mathcal{C}''_{24}$ are proposed optimum codes over $GF(4)$.

The weight enumerators of the codes $\mathcal{C}'_{24}$ and $\mathcal{C}''_{24}$ are

$$\begin{aligned} W_{\mathcal{C}'_{24}}(z) &= 1 + 528z^8 + 13992z^{10} + 171276z^{12} + 1118040z^{14} + 3773517z^{16} + 6218520z^{18} \\ &\quad +4413948z^{20} + 1034088z^{22} + 33306z^{24} \end{aligned}$$

$$\begin{aligned} W_{\mathcal{C}''_{24}}(z) &= 1 + 648z^8 + 13032z^{10} + 174636z^{12} + 1111320z^{14} + 3781917z^{16} + 6211800z^{18} \\ &\quad +4417308z^{20} + 1033128z^{22} + 33426z^{24} \end{aligned}$$

Applying the above method, we can obtain optimum graph codes over $GF(4)$ from the first two generator vector.

n	d	L_n	First row of generator matrix
16	6	6	$(\omega,1,1,0,1,0,0,0,1,0,0,0,1,0,1,1)$
22	8	8	$(\omega,1,1,0,1,0,1,0,0,0,0,0,1,0,0,0,0,1,0,1,0,1,1)$
16	6	6	$(\omega,1,0,1,0,1,0,0,1,0,0,1,0,1,0,1)$
19	7	7	$(\omega,1,1,0,1,0,0,0,1,1,0,0,0,1,0,1,1)$

3 New codes from dense circulant graphs

From the above section, we see that the circulant graphs under our consideration are all relatively sparse. So one may think that only sparse circulant graphs produce optimum graph codes. The following fact gives it a negative answer.

Danielsen [4] obtained an optimum additive code $(30, 2^{30}, 12)$ from the vector

$$\alpha_{30} = (\omega, 0, 1, 1, 0, 0, 0, 0, 1, 1, 0, 1, 1, 1, 1, 1, 1, 1, 1, 1, 0, 1, 1, 0, 0, 0, 0, 1, 1, 0),$$

which corresponds to a circulant graph of order 30 such that its adjacent matrix A_{30} is generated by the first row

$$\alpha_{30} = (0, 0, 1, 1, 0, 0, 0, 0, 1, 1, 0, 1, 1, 1, 1, 1, 1, 1, 1, 1, 0, 1, 1, 0, 0, 0, 0, 1, 1, 0).$$

It is clear that the circulant graph is 17-regular. Note that the order of this graph is 30, so the degree of each vertex is relatively large, i.e., it is a relatively dense graph. Let

$$\alpha_n = (\omega, 0, 1, 1, 0, 0, 0, 0, 1, 1, 0, \overbrace{1, 1, \ldots, 1, 1}^{n-21}, 0, 1, 1, 0, 0, 0, 0, 1, 1, 0).$$

For $n = 32$ and $n = 34$, we have the following vectors,

$$\alpha_{32} = (\omega, 0, 1, 1, 0, 0, 0, 0, 1, 1, 0, 1, 1, 1, 1, 1, 1, 1, 1, 1, 1, 0, 1, 1, 0, 0, 0, 0, 1, 1, 0),$$

$$\alpha_{34} = (\omega, 0, 1, 1, 0, 0, 0, 0, 1, 1, 0, 1, 1, 1, 1, 1, 1, 1, 1, 1, 1, 1, 1, 1, 0, 1, 1, 0, 0, 0, 0, 1, 1, 0).$$

By Algorithm 1, both $\mathcal{C}_{32}$ and $\mathcal{C}_{34}$ are proposed optimum codes over $GF(4)$.

The weight enumerators of the codes $\mathcal{C}_{32}$ and $\mathcal{C}_{34}$ are

$$\begin{aligned} W_{\mathcal{C}_{32}}(z) &= 1 + 1325z^{10} + 41973z^{12} + 745155z^{14} + 8030541z^{16} + 53150370z^{18} + 213875634z^{20} \\ &\quad +510617670z^{22} + 691665390z^{24} + 491629473z^{26} + 159600905z^{28} + 17838471z^{30} \\ &\quad +286740z^{32} \end{aligned}$$

$$\begin{aligned} W_{\mathcal{C}_{34}}(z) &= 1 + 492z^{10} + 14373z^{12} + 291849z^{14} + 3494061z^{16} + 26279603z^{18} + 123536402z^{20} \\ &\quad +357928154z^{22} + 620714798z^{24} + 614055698z^{26} + 319190777z^{28} + 75747789z^{30} \\ &\quad +6157556z^{32} + 72095z^{34} \end{aligned}$$

References

[1] J. C. Bermond, F. Comellas, D. F. Hsu, *Distributed loop computer networks: A survey*, J. Parallel Distributed Comput. 24 (1995), 2-10.

[2] F. T. Boesch, J. F. Wang, *Reliable circulant networks with minimum transmission delay*, IEEE Trans. Circuits Syst. 32(1985), 1286-1291.

[3] J. A. Bondy, U. S. R. Murty, *Graph Theory*, GTM 244, Springer, 2008.

[4] L. E. Danielsen, *On Self-Dual Quantum Codes*, Graphs and Boolean Functions, 2005.

[5] L. E. Danielsen, *Graph-based classification of self-dual additive codes over finite field*, Adv. Math. Commun. 3(4)(2009), 329-348.

[6] L. E. Danielsen, *On the Classification of Hermitian Self-Dual Additive Codes over GF(9)*, IEEE Trans. Inform. Theory 58(8)(2012), 5500-5511.

[7] L. E. Danielsen, M. G. Parker, *Directed Graph Representation of Half-Rate Additive Codes over GF(4)*, Des. Codes Cryptogr. 59(2011), 119-130.

[8] L. E. Danielsen, M. G. Parker, *On the classification of all self-dual additive codes over* $GF(4)$ *of length up to* 12, J. Combin. Theory, Series A, **113**(2006), 1351-1367.

[9] D. G. Glynn, T. A. Gulliver, J. G. Marks, M. K. Gupta, *The Geometry of Additive Quantum Codes*, Preface, Springer, 2006.

[10] W. C. Huffman, Vera Pless, *Fundamentals of Error-Correcting Codes*, Cambridge University, 2003.

[11] B. Mans, F. Pappalardi, I. Shparlinski, *On the spectral Adam property for circulant graphs*, Discrete Math. 254(1-3)(2002), 309-329.

[12] P. T. Meijer, *Connectivities and Diameters of Circulant Graps*, B.Sc.(Honors), Simon Fraser University, 1987.

[13] E. A. Monakhova, *A survey on undirected circulant graphs*, Discrete Mathematics, Algorithms and Applications, 4(1)(2012), DOI: 10.1142/S1793830912500024.

[14] M. E. Muzychuk, G. Tinhofer, *Recognizing circulant graphs of prime order in polynomial time*, Electron. J. Combin. 5(1)(1998), 501-528.

[15] W. A. Stein et al., *Sage Mathematics Software (Version 6.1.1)*, The Sage Development Team, 2014, http://www.sagemath.org.

[16] V. Tonchev, *Error-correcting codes from graphs*, Disrete Math., **257**(2002), 549-557.

[17] Z. Varbanov, *Additive circulent graph codes over GF(4)*, Math. Maced. 6(2008), 73-79.